

LNX-500AG Series

5-Port Industrial Gigabit Unmanaged Ethernet Switch, with 5*10/100/1000Tx



Features


- ▶ Supports 5-Port 10/100/1000Tx RJ45 Fast Ethernet
- ▶ Supports Auto MDI/MDI-X Function
- ▶ Store-and-Forward Switching Architecture
- ▶ 10Gbps Back-Plane (Switching Fabric)
- ▶ 8K MAC Address Table
- ▶ Surge Protection: 2,000 VDC Support
- ▶ ESD Protection: 6,000 VDC Support
- ▶ Redundant Power Input Design: 12~48VDC
- ▶ Built-in 1 Relay Output for Power Failure Warning
- ▶ IP30 Rugged Metal Case Design
- ▶ DIN-Rail and Wall Mount Support
- ▶ Operating Temperature Range - STD: -10° to 70° C, EOT: -40° to 75° C
- ▶ 5-Year Warranty

INTRODUCTION

Antaira Technologies' LNX-500AG industrial Gigabit unmanaged Ethernet switch series is IP30 rated and DIN-Rail mountable with 5*10/100/1000Tx, making it ideal for applications that demand a high bandwidth connectivity solution.

This series provides a high EFT and ESD protection that has a dual power input with a reverse power polarity protection. In addition, the built-in relay warning function alerts maintainers when power failures occur. There is a wide operating temperature model that supports -40 to 75°C. The LNX-500AG series is an ideal solution for harsh outdoor weather environments and industrial applications.

DIMENSIONS



SPECIFICATIONS

Technology	
Standards	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3az Gigabit Fiber
Processing Type	Store and Forward
Protocol	CSMA/CD
Flow Control	IEEE 802.3x back pressure flow control
Switch Properties	
Switch Architecture	Back-Plane (Switching Fabric): 10Gbps 14,880pps for Ethernet Port 148,800pps for Fast Ethernet Port 1,488,000pps for Gigabit Ethernet Port
Transfer Rate	
Memory Buffer	131 Kbits
Jumbo Frame	9.6Kbytes
MAC Table Size	8K
Interface	
Ethernet Port	5*10/100/1000Tx RJ45
Fiber Port	-
Network Cable	10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5 1000Base Tx: 2-pair UTP/STP Cat. 5/5E
Power Requirements	
Input Voltage	12~48VDC, Redundant Input
Overload Current Protection	Present
Connection	1 removable 6-contact terminal block
Reverse Polarity Protection	Yes
Power Consumption	5 Watts

Mechanical Characteristics	
Housing	Metal, IP30 protection
Dimensions	30 x 95 x 142 mm (W*D*H)
Weight	Unit: 1.0 lbs.; Shipping Weight: 1.5 lbs.
Mounting	DIN-Rail, wall mounting (optional)
Environmental Limits	
Operating Temperature	STD: -10° to 70° C EOT: -40° to 75° C
Storage Temperature	-40°C ~ 85°C
Ambient Relative Humidity	5 to 95%, (non-condensing)
Regulatory Approvals	
EMI	FCC Class A
EMS	EN61000-4-2,3,4,5,6,8, EN61000-6-2,4
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Certifications	FCC, CE, UL
Warranty	5 Years

ORDERING INFO

LNX-500AG	5-Port Industrial Gigabit Unmanaged Ethernet Switch, with 5*10/100/1000Tx
LNX-500AG-T	5-Port Industrial Gigabit Unmanaged Ethernet Switch, with 5*10/100/1000Tx ; EOT: -40° to 75°C

Optional Accessories

MDR-10-24	10W Industrial Din Rail Power Supply, 24VDC
DR-15-24	15W Industrial Din Rail Power Supply, 24VDC
DR-45-24	45W Industrial Din Rail Power Supply, 24VDC
DR-75-48	75W Industrial Din Rail Power Supply, 48VDC