Ref. No.:	PhO-BST-080
Date:	August 25, 2015

PRODUCT NOTICE

Dear Valued Customers,

The purpose of this product notice is to inform you that the following Antaira product model will be phased out on August 25, 2015.

Phase-Out Model Name:	**BST-080** 2.4GHz 800mW Wireless Signal Booster
Alternative Model Name:	**None**

Below, is the full phase-out schedule and information for the BST-080 series:

- **Phase-Out Notice:** Immediate
- **Phase-Out Start Date:** Immediate
- **Alternative Model Ship Date:** No offered alternative

This is an immediate Phase Out Notice for Antaira's **BST-080**, which is due to a declining demand for 2.4GHz signal boosters. This is because newer technology has allowed for more powerfull and efficent wireless radio construction, drastically reducing the need for the signal booster.

We appreciate your understanding and patience as we phase-out the BST-080. If your project still requires this discontinued product, please contact the Antaira Sales Team at 714-671-9000 or sales@antaira.com and they will initiate the appropriate action. Please note that all service rules (e.g., warranty) will still apply after this product is phased out.

Regards,

Antaira Technologies

SPECIFICATIONS

	OLD VERSION	ALTERNATIVE REPLACEMENT
Pictures		Not Applicable
Model Names	**BST-080**	
SPECIFICATIONS		
Frequency Band	2.4GHz ~ 2.5GHz	
Signal Type	DSSS	
TR Switch Time	1 µsec	
RF Connector Type	90° RP-SMA Male	
Antenna Connector	RP-SMA Female	
TX Linear Output Power	+24 dBm max @ 11g +29 dBm max @ 11b	
Diagnosis LED	RWP (Green), Tx (Red), Rx (Amber)	
DC Supply Voltage	6.0V	
Rx Input Power	-10dBm	
Tx Input Power	+20 dBm	
Operating Temperature	-0° ~ 50° C	
Storage Temperature	-40° ~ 90° C	
Dimensions (L x w x D)	155.0 x 21.6 x 36.8	
Weight	20g	